

Item no. 99901410

Connector type F-56-ALM 4.9/8.4
For cable Draka Coax 10 AD 10 S AL

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating (measured)	Cable data
(calculated)	Cable data
Transfer Impedance (CoMeT)	<2,5 mΩ/m @ 5-30MHz
	<0,1 mΩ/con. @ 5-30MHz
Shielding Effectiveness (CoMeT)	>130 dB @ 30-1000MHz
	>120 dB @ 1000-3000MHz



All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.

Return Loss (IEC 61169-1)
(Rhode und Schwarz ZVB-8)

0.3 - 500 MHz
500 - 860 MHz
860 - 1000 MHz
1000 - 1750 MHz
1750 - 2150 MHz
2150 - 3000 MHz

	Better than	Typical
	-33 dB	-35,6 dB
	-31 dB	-34,3 dB
	-30 dB	-33,3 dB
	-29 dB	-31,9 dB
	-29 dB	-31,7 dB
	-29 dB	-31,7 dB

Insertion Loss Max.

0.3 - 500 MHz
500 - 860 MHz
860 - 1000 MHz
1000 - 1750 MHz
1750 - 2150 MHz
2150 - 3000 MHz

	Better than	Typical
	-0,06 dB	-0,01 dB
	-0,07 dB	-0,02 dB
	-0,07 dB	-0,02 dB
	-0,07 dB	-0,02 dB
	-0,07 dB	-0,02 dB
	-0,08 dB	-0,03 dB

Temperature

Installing
Operating
Storing

-5° to +50° C
-40° to +100° C
-40° to +100° C

Intermodulation

3rd Order (@2x100mW)

IM3	IP3-value
<-145 dBc	>+92 dBm

Inner Conductor Resistance

(@ 1 A DC)

Cable data

Sealing Test

(IEC IP-code)

-

Insulation Resistance

(@ 500 VDC)

Cable data

O-rings

--

Dielectric Strength

DC Test Voltage

Cable data

Base Material

Body Parts
Inner Conductor

Brass CuZn39Pb3
-

Max. Tensile Strength

Overall

>392 N
>40 Kgf

Plating

Body Parts
Inner Conductor

Nitin-6
-

Torsional Strength

(Connector / Cable)

* NATM

Insulators

-

Test performed by

Date of release

Søren B. Sørensen
March 10, 2011

Remarks

* Not Able To Measure(NATM): The cable starts to twist without the connector loosing its grip.

ISO 9001:2008 / ISO 14001 certified

Distributor:

Corning Cabelcon Aps, Industriparken 10, DK 4760 Vordingborg
Tel: +45 55 98 55 99 · Fax: + 45 55 98 55 04
E-mail: cabelcon@cabelcon.dk · www.cabelcon.dk

CABELCON
connectors

Form 041 rev 8